

Product Information

Semi-volatile special solvent for cleaning paint-applying equipment, brushes, tools, metal surfaces, etc. Suitable for degreasing substrates.

| | | | | |
|--|---|-----------------|---------------------|---------------|
| Colour shade | colourless | | | |
| Mixing ratio | | | | |
| Hardener | | | | |
| Thinners | | | | |
| Spraying viscosity 20° C | | | | |
| Application | spraying pressure | spraying nozzle | spraying operations | |
| Air / Flowjar - Spray gun | | | | |
| Airless / Airmix | | | | |
| Pot life | | | | |
| Coat thickness / dry film | | | | |
| Curing time / Flash off time | | | | |
| Dry | recoat time | dust dry | set to touch | full hardness |
| Object Temp. 20° C Object Temp. 60° C | | | | |
| VOC-compliant | EC limiting value for the product (cat. B/a): 850 g/l (2007) This product contains max. 7.05 lbs/gal VOC | | | |

Safety instructions :

Keep containers tightly closed. Keep away from heat and flame, fire heat or other potential sources of ignition. The preparation may charge electrostatically. Always use earthing leads when taking out or transferring from one container to another.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.